



**PART NUMBER ORDERING CODE**

**MR386 - X X - XX**

**FIBER**  
**2** 62.5/125, TYPE OM1

**OPTICAL CIRCUIT AND MATERIAL**  
**0** MRI SAFE, NON-METALLIC, NO  
**4** MRI SAFE, NON METALLIC, NC  
**1** INDUSTRIAL, NO  
**5** INDUSTRIAL, NC

**OPTICAL PIGTAIL LENGTH**  
**1R5** LC DUPLEX PIGTAIL, 1.5m  
**03** LC DUPLEX PIGTAIL, 3m(STANDARD)  
**05** LC DUPLEX PIGTAIL, 5m  
**10** LC DUPLEX PIGTAIL, 10m

NOTE: OTHER LENGTHS UPON REQUEST

- 2 WARNING: KEEP CONNECTOR COVERS IN PLACE DURING STORAGE TO PROTECT FIBER OPTIC INTERFACES
- 1 WARNING: AVOID SHARP BENDS AND CABLE PINCHING. KEEP BEND RADIUS GREATER THAN 0.5 INCH [13MM].

NOTES: UNLESS OTHERWISE SPECIFIED

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MICRONOR INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MICRONOR INC. IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	MICRONOR INC. CAMARILLO, CA (805) 389-6600
DIMENSIONS ARE IN INCHES	DRAWN	A DU	4/22/16	
TOLERANCES:	CHECKED			TITLE:
FRACTIONAL ±	ENG APPR.			<b>FIBER OPTIC MICROSWITCH</b>
ANGULAR: MACH ±	MFG APPR.			SIZE DWG. NO. REV
BEND ±	Q.A.			<b>C MR386 A</b>
TWO PLACE DECIMAL ±.02	COMMENTS:			SCALE: 2:1 WEIGHT: SHEET 1 OF 1
THREE PLACE DECIMAL ±.004				
INTERPRET GEOMETRIC TOLERANCING PER:				
MATERIAL				
FINISH				
APPLICATION				